




Flange Sobreposto (Slip-ON) 400#



Item #	Diâmetro Nominal (Cota)	Diâmetro Externo (Ø)	Círculo de Furação (W)	Diâmetro Ressalto (K)	Espessura da Aba min WN, SW, SO - RF e FF, CE e TH (tf)	Espessura da Aba - Solto min LJ (tf)	Altura do Ressalto mm (R)	Altura do Ressalto in POL (R)
Ø95"	1/2	95	66.7	34.9	14.3	14.3	7	6.35
Ø115"	3/4	115	82.6	42.9	15.9	15.9	7	6.35
Ø125"	1	125	88.9	50.8	17.5	17.5	7	6.35
Ø135"	1.1/4	135	98.4	63.5	20.7	20.7	7	6.35
Ø155"	1.1/2	155	114.3	73.0	22.3	22.3	7	6.35
Ø165"	2	165	127.0	92.1	25.4	25.4	7	6.35
Ø190"	2.1/2	190	149.2	104.8	28.6	28.6	7	6.35
Ø210"	3	210	168.3	127.0	31.8	31.8	7	6.35
Ø230"	3.1/2	230	184.2	139.7	35.0	35.0	7	6.35
Ø255"	4	255	200.0	157.2	35.0	35.0	7	6.35
Ø280"	5	280	235.0	185.7	38.1	38.1	7	6.35
Ø320"	6	320	269.9	215.9	41.3	41.3	7	6.35
Ø380"	8	380	330.0	269.9	47.7	47.7	7	6.35
Ø445"	10	445	387.4	323.8	54.0	54.0	7	6.35
Ø520"	12	520	450.8	381.0	57.2	57.2	7	6.35
Ø585"	14	585	514.4	412.8	60.4	60.4	7	6.35
Ø650"	16	650	571.5	469.9	63.5	63.5	7	6.35
Ø710"	18	710	628.6	533.4	66.7	66.7	7	6.35
Ø775"	20	775	685.8	584.2	69.9	69.9	7	6.35
Ø915"	24	915	812.8	692.2	76.2	76.2	7	6.35